

	REMOVAL			PREPARATION						POLISHING					
NAME	PCD	ARROW	S-SEG	6-SEG	TWISTER	T-SEG	9 & 12 SEG	18 & 24 SEG	DOUBLE ROW	TURBO	BORIDE EASY EDGE	DRIFT DRY	REMI RES RING	REMI RES PAD	WHIP WET PAD
SIZE	5" NON-THREADED	5" BOTH	5" THREADED	-	5" NON-THREADED	-	4.5" BOTH	4.5" BOTH	4" BOTH	-	5" THREADED	5" VELCRO	- VELCRO	5" VELCRO	5" VELCRO
SIZE	7" BOTH	7" BOTH	7" THREADED	7" NON-THREADED	7" NON-THREADED	7" THREADED	7" BOTH	7" BOTH	7" THREADED	7" THREADED	7" THREADED	7" VELCRO	7" VELCRO	- VELCRO	7" VELCRO
HEIGHT	FULL PCD HEIGHT	3/8"	3/8"	1/4"	1/4"	1/4"	3/16"	3/16"	1/4"	1/4"	5/8"	3 MM	3 MM	3 MM	3 MM
GRIT	PCD	25/30	30/40	16/20	18/20 60/80 100/120	25/30	25/30	25/30	25/30	25/30	30, 50, 100, 270, 400	50, 100, 200, 400, 800, 1500, 3000	50, 100, 200, 400	50, 100, 200, 400	50, 100, 200, 400, 800 1500, 3000
BOND	FULL RND	SOFT	MEDIUM	SOFT	MEDIUM	MEDIUM	MED/HARD	MED/HARD	MED/HARD	MEDIUM	CERAMIC	RESIN	RESIN	RESIN	RESIN
METHOD	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	WET/DRY	DRY	WET/DRY	WET/DRY	WET
TASK	COATING REMOVAL	COATING REMOVAL & THINSET REMOVAL	LIGHT COATINGS REMOVAL	SMOOTH PROFILE FAST FLATTENING	HEAVY EXPOSURE	T-SEGS FOR UNEVEN SURFACES	MEDIUM EXPOSURE	LIGHT EXPOSURE	THIN SET REMOVAL	COUNTERTOP: STONE & CONCRETE	HONING	POLISHING	POLISHING	POLISHING	POLISHING

Metabo 4.5"
Scarifier
RFEV-19-125-RT



Metabo 5"
Renovation
Concrete Grinder
RSEV-19-125RT



Metabo
Hand Grinder
5": WEV-125-HT
7": W24-230-MVT



800.896.8665

www.runyonsurfaceprep.com